Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **Everclear 510 1:1 Komponente B**

· Article number: 11476, 11452_B, 11483

 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the

Hardening agent/ Curing agent mixture

· 1.3 Details of the supplier of the safety data sheet

AKEMI chemisch technische Spezialfabrik GmbH Manufacturer/Supplier:

Laboratory

Lechstrasse 28 D 90451 Nürnberg

Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de

· Further information obtainable from:

· 1.4 Emergency telephone

number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

+44 (171) 635 91 91

National Poison Inform. Centre

Medical Toxicology Unit

Avalonley Road London SE14 5ER

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07

· Signal word Warning

· Hazard-determining components

of labelling:

aliphatic polyisocyanate

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

4-isocyanatosulphonyltoluene

· Hazard statements H332 Harmful if inhaled.

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

> > (Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

. 3		
rade name: Everclear 510 1:1	Komponente B	
		(Contd. of page
· Precautionary statements	P101	If medical advice is needed, have product container or lab at hand.
	P102	Keep out of reach of children.
	P103	Read label before use.
	P261	Avoid breathing vapours.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves / eye protection.
	P302+P352	IF ON SKIN: Wash with plenty of water.
	P304+P340	IF INHALED: Remove person to fresh air and ke comfortable for breathing.
	P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minute Remove contact lenses, if present and easy to do. Contin rinsing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention
	P403+P233	Store in a well-ventilated place. Keep container tightly close
	P405 P501	Store locked up. Dispose of contents/container in accordance with loc regional/national/international regulations.
- Additional information:	Contains isocva	anates. May produce an allergic reaction.
· 2.3 Other hazards		, 1
· Results of PBT and vPvB asse	essment	
· PBT:	Not applicable.	
· vPvB:	Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17-0000	aliphatic polyisocyanate Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%	
CAS: 136210-30-5 ELINCS: 429-270-1 Index number: 607-521-00-8 Reg.nr.: 01-0000017556-64-0000	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate Skin Sens. 1, H317 Aquatic Chronic 3, H412	<10%	
CAS: 82985-35-1 EINECS: 280-084-5 Reg.nr.: 01-2119969956-12-xxxx	Bis(trimethoxysilylpropyl)amin Eye Dam. 1, H318	1-5%	
CAS: 4083-64-1 EINECS: 223-810-8 Index number: 615-012-00-7 Reg.nr.: 01-21199800050-47	4-isocyanatosulphonyltoluene Resp. Sens. 1, H334 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1%	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact:
 After eye contact:
 After swallowing:
 Immediately wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water.
 Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)



(Contd. of page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

 4.2 Most important symptoms and effects, both acute and

delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

 Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable

extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from

the substance or mixture In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx) Hydrogen cyanide (HCN)

5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage

system.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

Absorb with liquid-binding material (sand, diatomite, acid binders, universal containment and cleaning up:

binders, sawdust).

Ensure adequate ventilation.

See Section 7 for information on safe handling. · 6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: No special requirements.

· Information about storage in one

common storage facility: Not required.

(Contd. on page 4)



(Contd. of page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

Further information about storage

<u>conditions:</u> Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from frost.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

<u>design of technical facilities:</u> No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

4083-64-1 4-isocyanatosulphonyltoluene

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

· DNELs

Oral

Dermal

28182-81-2 aliphatic polyisocyanate

DNEL (Kurzzeit-akut)

Inhalative DNEL (Kurzzeit-akut)		1 mg/m³ Air (ARB)	
	DNEL (Langzeit-wiederholt)	0.5 mg/m ³ Air (ARB	

136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (ARB)
	1.4 mg/kg bw/day (BEV)

DNEL (Kurzzeit-akut) 1.4 mg/kg bw/day (BEV)
DNEL (Langzeit-wiederholt) 4 mg/kg bw/day (ARB)

1.4 mg/kg bw/day (BEV)

1.4 mg/kg bw/day (BEV)

Inhalative DNEL (Kurzzeit-akut) 112 mg/m³ Air (ARB)

DNEL (Langzeit-wiederholt)

4.8 mg/m³ Air (BEV)

28 mg/m³ Air (ARB)

4.8 mg/m³ Air (BEV)

82985-35-1 Bis(trimethoxysilylpropyl)amin

Oral	DNEL (Langzeit-wiederholt)	1.54 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	
		1.54 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	30.41 mg/m³ Air (ARB)
		5.36 mg/m³ Air (BEV)

· PNECs

28182-81-2 aliphatic polyisocyanate

PNEC (wässrig) 38.28 mg/l (KA)

0.0127 mg/l (MW) 0.127 mg/l (SW) 1.27 mg/l (WAS)

PNEC (fest) 53,200 mg/kg Trockengew (BO)

26,670 mg/kg Trockengew (MWS) 266,700 mg/kg Trockengew (SWS)

136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC (wässrig) 31.1 mg/l (KA)

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

(Contd. of page 4)

0.000013 mg/l (MW)

0.00013 mg/l (SW)

PNEC (fest) 0.1 mg/kg Trockengew (BO)

0.02 mg/kg Trockengew (MWS) 0.21 mg/kg Trockengew (SWS)

82985-35-1 Bis(trimethoxysilylpropyl)amin

PNEC (wässrig) 22 mg/l (KA)

0.02 mg/l (MW) 0.2 mg/l (SW) 2 mg/l (WAS)

PNEC (fest)

0.026 mg/kg Trockengew (BO) 0.072 mg/kg Trockengew (MWS) 0.72 mg/kg Trockengew (SWS)

Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic

measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A/P2

· Protection of hands:

· Material of gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell,

internet: http://www.kcl.de).

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butvl rubber, BR

Fluorocarbon rubber (Viton)

· Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

Eye protection:

(Contd. of page 5)

Tightly sealed goggles

• Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1	Information	on on	basic p	hysical a	and chem	nical properties

General Information

Appearance:

Form: Fluid
Colour: Colourless
Odour: Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Flash point: >160 °C

· Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

· Auto-ignition temperature: Not determined.

Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

Density at 20 °C:
Relative density
Vapour density
Evaporation rate
1.16 g/cm³
Not determined.
Not determined.
Not determined.

• Evaporation rate Not determine

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

Viscosity:

<u>Dynamic:</u> Not determined. <u>Kinematic:</u> Not determined.

· Solvent content:

Organic solvents: 0.0 %

Solids content: 5.0 %

• <u>9.2 Other information</u> No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)



(Contd. of page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

No dangerous reactions known.

reactions · 10.4 Conditions to avoid No further relevant information available. No further relevant information available. · 10.5 Incompatible materials:

10.6 Hazardous decomposition

· 10.3 Possibility of hazardous

No dangerous decomposition products known. products:

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Harmful if inhaled.

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 0.474 mg/l (rat)

28182-81-2 aliphatic polyisocyanate

Oral	LD50	>2,500 mg/kg (rat)
	NOAEL-Werte	3 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat) (OECD TG 403)

136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral	LD50	>2,000 mg/kg (rat) (Richtlinie 67/548/EWG, Anhang V, B.1.)
Dermal	LD50	>2,000 mg/kg (rat) (Richtlinie 67/548/EWG, Anhang V, B.3.)
Inhalativa	LC50/4h	4 224 mg/m2 (rot) (OECD Brüfrightlinig 402)

Inhalative LC50/4h >4,224 mg/m3 (rat) (OECD-Prüfrichtlinie 403)

82985-35-1 Bis(trimethoxysilylpropyl)amin

Oral	LD50	3,780 mg/kg (rat) (OECD 401)
	NOEL	3,780 mg/kg (rat) (OECD 401) 200 mg/kg (rat) (OECd 408)
Dermal	LD50	11,865 mg/kg (rabbit) (OECD 402)
		11,752 mg/kg (rat)
	NOEL	>84 mg/kg (rat) (OECD 410)

4083-64-1 4-isocyanatosulphonyltoluene

Orai	LD50	2,600 mg/kg (rat)
------	------	-------------------

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

 Serious eye damage/irritation Causes serious eye irritation. May cause an allergic skin reaction. Respiratory or skin sensitisation

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

 Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Reproductive toxicity

· STOT-single exposure May cause respiratory irritation.

· STOT-repeated exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · Aspiration hazard

SECTION 12: Ecological information

· 12.1 Toxicity

quati	

28182-81-2	aliphatic	polvisocy	vanate
------------	-----------	-----------	--------

3,828 mg/l (BES) (OECD 209) EC50

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

mining date in	7 6161611 Manuaer 2	11011010111 1011112
rade name: E	Everclear 510 1:1 Komponente B	
		(Contd. of pag
LC 0/96h	>82.8 mg/l (Brachydanio rerio) (OECD 203)	
EC50/48h	127 mg/l (daphnia magna) (RL 67/548/EWG, Anhang V, C.3.)	
ErC50/72h	, , ,	
EC0	>100 mg/l (daphnia magna) (OECD 202)	
EL50/48h	127 mg/l (daphnia magna)	
LL50/96h	8.9 mg/l (Brachydanio rerio)	
EC10	370 mg/l (Desmodesmus subspicatus)	
EC50/72h	>100 mg/l (Scenedesmus subspicatus) (OECD 201)	
LC50/96h	>100 mg/l (Danio rerio.) (RL 67/548/EWG, Anhang V, C.1.)	
136210-30	5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	
EC50	3,110 mg/l (BES) (ISO Vorschrift 8192-1986 E)	
IC50/72h	113 mg/l (Scenedesmus subspicatus) (Richtlinie 67/548/EWG, Anhang V, C.3.)	
EC50/48h	88.6 mg/l (daphnia magna) (UBA-Verfahrensvorschlag Mai 1984)	
ErC50/72h	113 mg/l (Scenedesmus subspicatus)	
NOEC	100 mg/kg (Ac) (OECD 208)	
	100 mg/kg (As) (OECD 208)	
	100 mg/kg (Bn) (OECD 208)	
	≥1,000 mg/kg (Eisenia fetida (Regenwürmer)) (OECD-Prüfrichtlinie 207)	
NOEC/21d	0.01 mg/l (daphnia magna) (Richtlinie 67/548/EWG, Anhang V, C.20.)	
LC50/96h	66 mg/l (Danio rerio.) (OECD 203)	
	Bis(trimethoxysilylpropyl)amin	
EC50	1,000 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)	
EC50/48h	>100 mg/l (daphnia magna)	
EC50/72h	>100 mg/l (Desmodesmus subspicatus)	
LC50/96h	100 mg/l (Oncorhynchus mykiss)	
	130 mg/l (Salmo gairdneri)	
	4-isocyanatosulphonyltoluene	
EC50/72h	23 mg/l (green alge)	
	150 mg/l (daphnia magna)	
LC50/96h	435 mg/l (piscis)	
 12.2 Persis degradabil 		
Otherinform	The product is not easily binderys debte	

degradability
 Other information:
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

Remark: Harmful to fish

· Additional ecological information:

• General notes: Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

· 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void			
· 14.2 UN proper shipping name				
· ADR, ADN, IMDG, IATA	Void			
· 14.3 Transport hazard class(es)				
· ADR, ADN, IMDG, IATA				
· <u>Class</u>	Void			
· 14.4 Packing group				
· <u>ADR, IMDG, IATA</u>	Void			
· 14.5 Environmental hazards:				
· Marine pollutant:	No			
· 14.6 Special precautions for user	Not applicable.			
· 14.7 Transport in bulk according to Annex II of				
Marpol and the IBC Code	Not applicable.			
· Transport/Additional information:	Not dangerous according to the above specifications.			
· UN "Model Regulation":	Void			

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

- VOC EU 0.1 g/l

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
 H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 19.11.2019 Version number 2 Revision: 19.11.2019

Trade name: Everclear 510 1:1 Komponente B

(Contd. of page 9)

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Laboratory

· Contact: Dieter Zimmermann

Elke Hake

Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB