
Technical Data Sheet

Page 1 of 1

Properties:	AKEMI® Solvent is product based on low boiling polar solvents. The product is characterized by the following properties: - very good dissolving properties of the paint applied to the AKEMI® Ceramic Colour Cards - very short evaporation time - free of methanol, chlorinated hydrocarbons and paraffinic components
Application Area:	AKEMI® Solvent is used to dissolve the paint applied to the AKEMI® Ceramic Colour Cards.
Instructions for use:	1. Apply undiluted with a fine brush to an area of approx. 1 cm² on the printed side of the AKEMI® Ceramic Colour Cards. 2. Dissolve the paint with the brush in a circular motion for approx. 5 - 10 seconds. 3. Apply the paint solution with a brush to the hardened PLATINUM P+ and allow to dry.
Special Notes:	- For professional use only. - Use AKEMI® Liquid Glove to protect your hands. - Use only on cold surfaces. Warm surfaces extremely accelerate the evaporation time of the solvent and thus deteriorate the dissolving capacity. - Optimum working temperature 15 - 25°C. - For proper waste disposal, the container must be completely emptied. - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
Technical Data:	Colour: colourless, clear Density: 0.87 g/cm³
Storage:	If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 5 years from production.
Health & Safety:	Read Safety Data Sheet before handling or using this product.
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 01.25