

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Primer AP 30**

Article number: 45025, 45026

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

*

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:toluene
ethyl acetate
propan-2-ol· Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H361d Suspected of damaging the unborn child.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapours.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains n-butyl methacrylate, methyl methacrylate. May produce an allergic reaction.

· **2.3 Other hazards**· Results of PBT and vPvB assessment· PBT: Not applicable.· vPvB: Not applicable.**SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 2)

CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 Reg.nr.: 01-2119471310-51	toluene Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	12.5-25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butanol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5 Reg.nr.: 01-2119486394-28-xxxx	n-butyl methacrylate Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<1%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<1%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents

aromatic hydrocarbons

≥15 - <30%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

· General information:

Immediately remove any clothing soiled by the product.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Supply fresh air; consult doctor in case of complaints.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

If skin irritation continues, consult a doctor.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Nausea

· Information for doctor:

Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.

b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.

Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.: Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.
Provide floor trough without outlet.
Store only in the original receptacle.
Store in a cool location.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

71-36-3 butanol

WEL Short-term value: 154 mg/m³, 50 ppm
Sk

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm
Long-term value: 208 mg/m³, 50 ppm

· DNELs

141-78-6 ethyl acetate

Oral	DNEL (Langzeit-wiederholt)	4.5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	63 mg/kg bw/day (ARB)
		37 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,468 mg/m ³ Air (ARB)
		734 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	734 mg/m ³ Air (ARB)
		367 mg/m ³ Air (BEV)

67-63-0 propan-2-ol

Oral	DNEL (Langzeit-wiederholt)	26 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	888 mg/kg bw/day (ARB)
		319 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	500 mg/m ³ Air (ARB)
		89 mg/m ³ Air (BEV)

108-88-3 toluene

Oral	DNEL (Langzeit-wiederholt)	8.13 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	384 mg/kg bw/day (ARB)
		226 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	384 mg/m ³ Air (ARB)
		226 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	192 mg/m ³ Air (ARB)
		56.5 mg/m ³ Air (BEV)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 5)

71-36-3 butanol

Oral	DNEL (Langzeit-wiederholt)	3.125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m ³ Air (ARB) 55 mg/m ³ Air (BEV)

80-62-6 methyl methacrylate

Oral	DNEL (Kurzzeit-akut)	0.25 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	1.5 mg/kg bw/day (ARB) 1.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1.5-13.67 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	1.5-8.2 mg/kg bw/day (BEV) 29.6-416 mg/m ³ Air (ARB) 6.3-104 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	208 mg/m ³ Air (ARB) 74.3-104 mg/m ³ Air (BEV)

· PNECs

141-78-6 ethyl acetate

PNEC (wässrig)	650 mg/l (KA) 0.024 mg/l (MW) 0.24 mg/l (SW) 1.65 mg/l (WAS)
PNEC (fest)	0.148 mg/kg Trockengew (BO) 0.115 mg/kg Trockengew (MWS) 1.15 mg/kg Trockengew (SWS)

67-63-0 propan-2-ol

PNEC (wässrig)	2,251 mg/l (KA) 140.9 mg/l (MW) 140.9 mg/l (SW) 140.9 mg/l (WAS)
PNEC (fest)	28 mg/kg Trockengew (BO) 552 mg/kg Trockengew (MWS) 552 mg/kg Trockengew (SWS)

108-88-3 toluene

PNEC (wässrig)	13.61 mg/l (KA) 0.68 mg/l (MW) 0.68 mg/l (SW) 0.68 mg/l (WAS)
PNEC (fest)	2.89 mg/kg Trockengew (BO) 16.39 mg/kg Trockengew (MWS) 16.39 mg/kg Trockengew (SWS)

71-36-3 butanol

PNEC (wässrig)	2,476 mg/l (KA) 0.008 mg/l (MW) 0.082 mg/l (SW) 2.25 mg/l (WAS)
PNEC (fest)	0.015 mg/kg Trockengew (BO) 0.018 mg/kg Trockengew (MWS)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 6)

	0.178 mg/kg Trockengew (SWS)
80-62-6 methyl methacrylate	
PNEC (wässrig)	10 mg/l (KA) 0.94 mg/l (MW) 0.094 mg/l (SW) 0.15-0.94 mg/l (WAS)
PNEC (fest)	1.47 mg/kg Trockengew (BO) 0.73-45.38 mg/kg Trockengew (MWS) 5.74 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.

· Respiratory protection:

Avoid contact with the eyes and skin.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR
Fluorocarbon rubber (Viton)
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level $\leq$ 2, 60 min
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Leather gloves
Strong material gloves

· Eye protection:



Tightly sealed goggles

· Body protection:

Protective work clothing

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Fluid

Colour:

Colourless

· Odour:

Specific type

· pH-value at 20 °C:

7

· Change in condition

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: > 76 °C

· Flash point:

-4 °C

· Ignition temperature:

425 °C

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:

1.2 Vol %

Upper:

12 Vol %

· Vapour pressure at 20 °C:

97 hPa

· Density:

Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic:

Not determined.

Kinematic at 20 °C:

7 mm²/s

· Solvent content:

Organic solvents:

94.5 %

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

No dangerous reactions known.

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Based on available data, the classification criteria are not met.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 8)

· LD/LC50 values relevant for classification:

141-78-6 ethyl acetate

Oral	LD50	4,100 mg/kg (mouse) 5,620 mg/kg (rat) 4,934 mg/kg (rbt)
	NOAEL-Werte	900 mg/kg (rat)
Dermal	LD50	>18,000 mg/kg (rabbit)
Inhalative	LC50	58 mg/l (rat)
	LC50/4 h	1,600 mg/l (rat)
	LC50/1h	200 mg/l (rat)
	LC50/8h	5.86 mg/l (rat)
	LC50/48h	333 mg/l (Leuciscus idus)

67-63-0 propan-2-ol

Oral	LD50	>2,000 mg/kg (rabbit) 5,840 mg/kg (rat) (OECD 401)
	NOAEL-Werte	400 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	47.5 ppm (rat)
	LC50/4 h	30-46.5 mg/l (rat)
	LC50	25,000 mg/m3 (rat)
	LC50/48h	>100 mg/l (Leuciscus idus)

108-88-3 toluene

Oral	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mus)
		25.7-30 mg/l (rat)

71-36-3 butanol

Oral	LD50	3,430 mg/kg (rabbit) (OECD 402) 2,292 mg/kg (rat) (OECD 401)
	LD50	3,400 mg/kg (rbt)
Inhalative	LC50/4 h	8,000 mg/l (rat)

97-88-1 n-butyl methacrylate

Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rbt) (OECD 402)
Inhalative	LC50/4 h	29 mg/l (rat) (OECD 403)

80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	4,632 mg/m3 (rat)
	LC50/4 h	29.8 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 9)

- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****141-78-6 ethyl acetate**

EC50/96h	220 mg/l (Pimephales promelas)
EC10/18h	2,900 mg/l (pseudomonas putida)
EC50/48h	610 mg/l (daphnia magna) (DIN 38412)
	5,600 mg/l (Desmodesmus subspicatus)
IC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC 0	29.3 mg/l (rat)
NOELR/72h	>100 mg/l (Desmodesmus subspicatus)
NOEC/21d	2.4 mg/l (daphnia magna)
EC10	2,900 mg/l (pseudomonas putida)
EC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC50/96h	230 mg/l (Oncorhynchus mykiss)
	230 mg/l (Pimephales promelas)

67-63-0 propan-2-ol

EC50/24h	9,714 mg/l (daphnia magna)
EC50	>1,000 mg/l (BES)
LC50/24h	9,714 mg/l (daphnia magna)
EC50/15min	22,000 mg/l (Photobac. phosphoreum)
IC50/72h	>1,000 mg/l (Desmodesmus subspicatus)
EC10/18h	5,175 mg/l (pseudomonas putida) (DIN 38412)
EC50/48h	13,299 mg/l (daphnia magna)
EC50/72h	>1,000 mg/l (green alge)
	>100 mg/l (Scenedesmus subspicatus)
LC50/96h	6,550 mg/l (piscis)
	9,640 mg/l (Pimephales promelas)

108-88-3 toluene

EC50/24h	84 mg/l (BES)
EC50/96h	>433 mg/l (Pseudokirchneriella subcapitata)
IC50/72h	12 mg/l (Pseudokirchneriella subcapitata) (lit.)
	12 mg/l (Selenastrum capricornutum) (lit.)
EC50/48h	5.46-11.5 mg/l (daphnia magna) (lit.)
NOEC	0.74 mg/kg (daphnia magna)
EC50/48h	3.78 mg/l (daphnia magna)
EC50/72h	10 mg/l (green alge)
	12.5 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	5.5 mg/l (piscis)
	11-15 mg/l (lem)
	5.8-17 mg/l (Oncorhynchus mykiss) (lit.)
	54 mg/l (Oryzias latipes)

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 10)

	12.6-19.05 mg/l (pimephales promelas) 7-28.2 mg/l (poecilia reticulata)
71-36-3 butanol	
EC50/96h	225 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50	4,400 mg/l (pseudomonas putida)
IC50/72h	>500 mg/l (Desmodesmus subspicatus)
NOEC/21d	4.1 mg/l (daphnia magna)
EC50/48h	1,328 mg/l (daphnia magna) (OECD 202)
EC50/72h	8,500 mg/l (green alge)
LC50/96h	1,200 mg/l (Leuciscus idus) 1,376 mg/l (pimephales promelas) (OECD 203) >500 mg/l (Scenedesmus subspicatus)
97-88-1 n-butyl methacrylate	
EC50/96h	57 mg/l (Pseudokirchneriella subcapitata)
EC50	253.6 mg/l (pseudomonas putida) (lit.)
IC50/72h	31.2 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/48h	32 mg/l (daphnia magna)
EC50/48h	25.4 mg/l (daphnia magna) (OECD 202)
LC50/96h	11 mg/l (piscis) 5.57 mg/l (Oryzias latipes) (OECD 203)
80-62-6 methyl methacrylate	
EC50/96h	170 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	69 mg/l (daphnia magna) (OECD 202)
EC0	100 mg/l (pseudomonas putida)
NOEC	9.4 mg/kg (Danio rerio.) (OECD 210)
NOEC/21d	37 mg/l (daphnia magna) (OECD 202)
EC50/72h	>110 mg/l (Selenastrum capricornutum)
LC50/96h	153.9-341.8 mg/l (lem) >79 mg/l (Oncorhynchus mykiss) (OECD 203) 125-275 mg/l (pimephales promelas) 326.4-426.9 mg/l (poecilia reticulata)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:**

Toxic for fish

· **Additional ecological information:**

· **General notes:**

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 11)

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 01 00	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)
16 01 99	wastes not otherwise specified

· Uncleaned packaging:· Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information· **14.1 UN-Number**· ADR, IMDG, IATA

UN1993

· **14.2 UN proper shipping name**· ADR

1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (ETHYL ACETATE, TOLUENE)

· IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, TOLUENE)

· **14.3 Transport hazard class(es)**· ADR· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA· Class

3 Flammable liquids.

· Label

3

· **14.4 Packing group**· ADR, IMDG, IATA

II

· **14.5 Environmental hazards:**· Marine pollutant:

No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· Danger code (Kemler):

33

· EMS Number:

F-E, S-E

· Stowage Category

B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 12)

· Transport/Additional information:

- ADR
- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- Transport category 2
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (ETHYL ACETATE, TOLUENE), 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 950.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.06.2019

Version number 5

Revision: 24.06.2019

Trade name: Primer AP 30

(Contd. of page 13)

- Recommended restriction of use
 - Department issuing SDS:
 - Contact:
 - Abbreviations and acronyms:
 - * Data compared to the previous version altered.
- H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 refer to Technical Data Sheet (TDS)
- Laboratory
 Dieter Zimmermann
 Elke Hake
 Fon ++49 (0)911 64296-59
 @mail E.Hake@akemi.de
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
- Adaptation in accordance with REACH directive 1907/2006/EC