

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Turbo Gloss 2K-UHS Clearcoat 2:1**

Article number: 70601, 70602

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Clear coating material, Varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Warning

Hazard-determining components of labelling:

n-butyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 1)

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
 Contains poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -hydroxy-, bis(1,2,2,6,6-Pentamethyl-piperidyl)sebacat, pentaerythritol tetrakis(3-mercaptopropionate), methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate. May produce an allergic reaction.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	12.5-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-211947591-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	<12.5%
EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336	1-5%
CAS: 104810-48-2	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -hydroxy- ⚠ STOT RE 2, H373 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Sens. 1, H317	<1%
CAS: 41556-26-7 Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-Pentamethyl-piperidyl)sebacat ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Sens. 1, H317	<1%

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31









Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 2)

CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23-0000	pentaerythritol tetrakis(3-mercaptopropionate)  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	<1%
CAS: 82919-37-7 EINECS: 280-060-4	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Skin Sens. 1, H317	<1%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-0000 01-2119463586-28	Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Induce vomiting only, if affected person is fully conscious.
If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

- Information for doctor: Breathing difficulty
Headache
Dizziness
Dizziness
Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.
- Hazards Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 3)

- Carbon monoxide (CO)
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
 - Protective equipment: Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
 - Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection: Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Store receptacle in a well ventilated area.
Store in a cool place.
Keep container tightly sealed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)

WEL	Long-term value: 350 mg/m ³
-----	--

· DNELs

Hydrocarbons, C9, aromatics

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (ARB)
		11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	100 mg/m ³ Air (ARB)
		32 mg/m ³ Air (BEV)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:
· General protective and hygienic measures:

Avoid close or long term contact with the skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 5)

compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level \leq 3, 60 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection:

Protective work clothing

* **SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:Form:

Fluid

Colour:

Colourless

· Odour:

Specific type

· Change in conditionMelting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 124-128 °C· Flash point:

>23 °C

· Ignition temperature:

315 °C

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:Lower:

1.5 Vol %

Upper:

10.8 Vol %

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 6)

· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	1 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	35 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	39,3 %
Solids content:	58,5 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Reacts with strong acids.
 - Reacts with strong alkali.
 - Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Nitrogen oxides (NO_x)
 - Possible in traces.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C9, aromatics

Oral	LD50	3,492 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>6,193 mg/l (rat)

7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1· Aspiration hazard

Based on available data, the classification criteria are not met.

(Contd. of page 7)

SECTION 12: Ecological information· **12.1 Toxicity**· Aquatic toxicity:**Hydrocarbons, C9, aromatics**

LC50	1-10 mg/l (daphnia magna)
EL50/48h	3.2 mg/l (daphnia magna) (OECD 202)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata)
	2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	7.4 mg/l (daphnia magna)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· Additional ecological information:· General notes:Do not allow product to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water· **12.5 Results of PBT and vPvB assessment**· PBT:

Not applicable.

· vPvB:

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents:

Alcohol

SECTION 14: Transport information· **14.1 UN-Number**

· ADR, IMDG, IATA

UN1263

· **14.2 UN proper shipping name**

· ADR

1263 PAINT

· IMDG, IATA

PAINT

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Flammable liquids.
· Danger code (Kemler): 30
· EMS Number: F-E, S-E
· Stowage Category A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· Transport category 3
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

P5c FLAMMABLE LIQUIDS

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 9)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- VOC EU 392.7 g/l
- DECOPAINT: subject to EU-regulations 2004/42/EG (ANNEX II) EU limit for this product (product-category (Kat. B/d)): 420g/l (2010). The ready-to-use product (comprises of clear lacquer and hardener) contains max. 420 g/l VOC.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2018

Version number 8

Revision: 09.01.2018

Trade name: Turbo Gloss 2K-UHS Clearcoat 2:1

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
REACH directive 1907/2006/EC

- Sources
- * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB