Safety data sheet according to 1907/2006/EC, Article 31

AKEMI®

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Akepox 2010 Component B

· Article number: 10616, 10623, 10624, 10627, 10598, 10615, 10643, 10644, 10645

 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the

mixture Epoxy resin adhesive

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Lechstrasse 28 D 90451 Nürnberg Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de

Further information obtainable from:

· 1.4 Emergency telephone

Laboratory

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

+44 (171) 635 91 91

National Poison Inform. Centre

Medical Toxicology Unit Avalonley Road London SE14 5ER

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



number:

GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects.

Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



(Contd. of page 1)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

· Hazard pictograms









GHS05 GHS07 GHS08 GHS09

· Signal word

Danger

Hazard-determining components

of labelling:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-

trimethylcyclohexylamine

Benzyl alcohol

4-nonylphenol, branched

formaldehyde polymer with 1,3-benzenedimethanamine and phenol

m-phenylenebis(methylamine)

N-(3-(trimethoxysilyl)propyl)ethylenediamine 3-aminomethyl-3,5,5-trimethylcyclohexylamine

· Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.H341 Suspected of causing genetic defects.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn

child.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label

at hand.

P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	
	/Con	td on nogo 2\

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

	(00	antal of nage
CAS: 57214-10-5 NLP: 500-137-0	formaldehyde polymer with 1,3-benzenedimethanamine and phenol Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ntd. of page 12.5-25
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	12.5-25
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<10%
CAS: 84852-15-3 EINECS: 284-325-5 Index number: 601-053-00-8 Reg.nr.: 01-2119510715-45-xxxx	4-nonylphenol, branched Acute Tox. 3, H331 Repr. 2, H361fd Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302	1-5%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid Eye Dam. 1, H318 Acute Tox. 4, H302	1-5%
CAS: 108-95-2 EINECS: 203-632-7 Index number: 604-001-00-2 Reg.nr.: 01-2119471329-32	phenol Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Muta. 2, H341; STOT RE 2, H373 Skin Corr. 1B, H314	1-5%
	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318 Skin Sens. 1, H317	1-5%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-0000	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<1%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

Supply fresh air and to be sure call for a doctor. · After inhalation:

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

· After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 4)



(Contd. of page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

• 4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness

Dizziness Nausea

Breathing difficulty

· Information for doctor:

The symptoms of phenol based poisoning appearances are white coloured mouth scabs, shock condition, insensibility, bradycardia and renal dysfunction and damage of renal tissue. Appropriate therapy measures: Administration of an adequate volume of liquid, gastrolavage in application of carbo medicinalis, sodium sulphate with plenty of water, infusion of glucose solution (5%); maesures against state of shock, hemodialysis.

Nonylphenol based exposition: causes corrosive burns, damages respiratory tract, eyes, skin and digestive system up to complete tissue destruction. Temporary dysfunctions such as dizziness, headache, nausea and diarrhea may occur. Can cause health disturbances like dermal bleaching, renal and hepatic demage.

damage.

Amines: Inhalation, swallowing or dermal contact may cause health damages. Cause burns, harm respiratory tract, eyes, skin, and digestion system in worst case up to complete destruction. Intermediate interferences such as headache, nausea, cough, dyspnea may occur. May cause allergies. Sensitized users may react towards very low amine concentrations and should avoid any further contact with this group of chemicals.

Hazards

Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special

treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

• 5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

Mount respiratory protective device.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage

vstem

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

• **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

(Contd. of page 4)

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class:

No further relevant information available. · 7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-95-2 phenol

WEL Short-term value: 16 mg/m³, 4 ppm

Long-term value: 7.8 mg/m³, 2 ppm

· DNELs

57214-10-5 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

DNEL (Kurzzeit-akut) 3.33 mg/kg bw/day (BEV) Oral DNEL (Langzeit-wiederholt) 3.33 mg/kg bw/day (BEV)

Dermal DNEL (Kurzzeit-akut)

0.00385-2.8 mg/kg bw/day (ARB)

(Contd. on page 6)

Printing date 12.07.2018



Safety data sheet according to 1907/2006/EC, Article 31

Version number 7 Revision: 12.07.2018

illing date i	2.07.2010	Version number 7	1\eVision. 12.07.2	
de name:	Akepox 2010 Component	В		
	· ·		(Contd. of pag	
		0.000167-0.008 mg/kg bw/day (BEV)	(Conta. or pag	
	DNEL (Langzeit-wiederho	3 3 , ,		
	(_agaa.a	0.000167-0.008 mg/kg bw/day (BEV)		
Inhalative	DNEL (Kurzzeit-akut)	2-6 mg/m³ Air (ARB)		
	Benzyl alcohol	2 0 mg/m / / (//(D)		
Oral	DNEL (Kurzzeit-akut)	25 mg/kg bw/day (BEV)		
	DNEL (Langzeit-wiederhol	, , ,		
Dermal	DNEL (Kurzzeit-akut)	47 mg/kg bw/day (ARB)		
Donnar	BITEL (Italizzon anal)	28.5 mg/kg bw/day (BEV)		
	DNEL (Langzeit-wiederho			
	DNLL (Langzen-wiedenic	5.7 mg/kg bw/day (AKB)		
Inhalativa	DNEL (Kurzzeit ekut)	450 mg/m³ Air (ARB)		
mnaiauve	DNEL (Kurzzeit-akut)	, ,		
	DNEL (Language Controlled	40.55 mg/m³ Air (BEV)		
	DNEL (Langzeit-wiederhol	, ,		
		8.11 mg/m³ Air (BEV)		
1477-55-0 Dermal	m-phenylenebis(methyla	•		
	, -	lt) 0.33 mg/kg bw/day (ARB)		
	DNEL (Langzeit-wiederhol 3 4-nonylphenol, branche	, ,		
	• • •	lt) 7.5 mg/kg bw/day (ARB)		
	DNEL (Langzeit-wiederhol			
108-95-2 p	` •	i) 0.5 mg/m² Ali (AKB)		
Oral	DNEL (Langzeit-wiederhol	t) 0.4 mg/kg bw/day (BEV)		
Dermal	, -	.		
	DNEL (Langzeit-wiederho	, , ,		
mnaiauve	DNEL (Langzeit-wiederhol	, ,		
		1.32 mg/m³ Air (BEV)		
PNECs	.			
	• • •	with 1,3-benzenedimethanamine and phenol		
PINEC (wa	ssrig) 30 mg/l (KA)			
	0.002 mg/l (MW)			
DNEO "	0.02 mg/l (SW)	(00)		
PNEC (fes	,			
	0.01 mg/kg Trocken			
0.1001 mg/kg Trockengew (SWS)				
	Benzyl alcohol			
PNEC (wä	ssrig) 39 mg/l (KA)			
	0.1 mg/l (MW)			
	1 mg/l (SW)			
	2.3 mg/I (WAS)			
PNEC (fes	,	- , ,		
	0.527 mg/kg Trocke	ngew (MWS)		
5.27 mg/kg Trockengew (SWS)		- , ,		
	m-phenylenebis(methyla	mine)		
PNEC (wä	ssrig) 0.0094 mg/l (MW)			
	0.094 mg/l (SW)		<u>, -</u>	
			(Contd. on pag	



(Contd. of page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

108-95-2 phenol

PNEC (wässrig) 2.1 mg/l (KA)

0.00077 mg/l (MW)

0.0077 mg/l (SW)

PNEC (fest) 0.136 mg/kg Trockengew (BO)

0.00915 mg/kg Trockengew (MWS) 0.0915 mg/kg Trockengew (SWS)

Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Protection of hands:

· Personal protective equipment:

General protective and hygienic

measures:

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

 $\cdot \, \underline{\text{Respiratory protection:}} \qquad \qquad \text{Not necessary if room is well-ventilated.}$

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

 Material of gloves Butyl rubber, BR (Contd. of page 7)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked

prior to the application.

Value for the permeation: Level \leq 6, 480 min Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

 For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

Dermatril (Art_No. 740, 741, 742)

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

· As protection from splashes gloves made of the following materials are

suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR

Camapren (KCL, Art No. 720, 722, 726)

· Not suitable are gloves made of

the following materials:

Natural rubber, NR

Fluorocarbon rubber (Viton)

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Appearance:

Form: **Pasty** Colour: Light yellow Odour: Characteristic

pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 205 °C

101 °C · Flash point:

· Ignition temperature: 380 °C

> 250 °C · Decomposition temperature:

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B				
		(Contd. of page 8)		
- Explosion limits:				
Lower:	1.3 Vol %			
<u>Upper:</u>	13 Vol %			
· Vapour pressure at 20 °C:	0.1 hPa			
- Density at 20 °C:	1.08 g/cm³			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
- Solvent content:				
Organic solvents:	11.5 %			
Solids content:	84.7 %			
· 9.2 Other information	No further relevant information available.			

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous

reactions

Strong exothermic reaction with acids.

Reacts with strong oxidising agents.

· 10.4 Conditions to avoid

· 10.5 Incompatible materials:

No further relevant information available. No further relevant information available.

10.6 Hazardous decomposition

products: Corrosive gases/vapours

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Harmful if inhaled.

ı	· LD/LC50 V	LD/LC50 values relevant for classification.				
	ATE (Acu	te Toxicity	Estimates)			
	Oral	LD50	2,575 mg/kg			
	Dermal	LD50	8,753 mg/kg			
	Inhalative	LC50/4 h	12.9-13.6 mg/l			

57214-10	-5 formalde	ehyde polymer with 1,3-benzenedimethanamine and phenol
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,020 mg/kg (rat)
100-51-6	Benzyl alc	ohol
Oral	LD50	1,040 mg/kg (mouse)
		1,040 mg/kg (rabbit)
		1,620 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	11 mg/l (rat)

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name:	Akepox 2010	Component B

		(Contd. of page 9)
	LC50/48h	360 mg/l (daphnia magna)
		645 mg/l (goo)
1477-55-0	m-phenyl	enebis(methylamine)
Oral	LD50	930 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	2.4 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)
84852-15-	3 4-nonylp	henol, branched
Oral	LD50	1,210 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	3.636 mg/l (mouse)
108-95-2 բ	ohenol	
Oral	LD50	300 mg/kg (mouse)
		317 mg/kg (rat)
Dermal	LD50	630 mg/kg (rat)
Inhalative	LC50/4 h	316 mg/l (rat)
5	LC50/8h	0.9 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation
 Respiratory or skin sensitisation
 CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 Germ cell mutagenicity
 Causes serious eye damage.
 May cause an allergic skin reaction.
 Suspected of causing genetic defects.

• Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

 Aquatic toxic 	· Aquatic toxicity:			
	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine			
EC50	>1,000 mg/l (BES)			
EL50/48h	11.1 mg/l (daphnia magna)			
EL50/72h	79.4 mg/l (Pseudokirchneriella subcapitata)			
LL50/96h	70.7 mg/l (Oncorhynchus mykiss)			
57214-10-5	57214-10-5 formaldehyde polymer with 1,3-benzenedimethanamine and phenol			
EC50	491.3 mg/l (BES)			
EC50/48h	29.8 mg/l (daphnia magna)			
EC50/72h	20.4 mg/l (Pseudokirchneriella subcapitata)			
LC50/96h	25.9 mg/l (Oncorhynchus mykiss)			
100-51-6 Benzyl alcohol				
EC50/24h	55-400 mg/l (daphnia magna)			
EC50/96h	640 mg/l (Scenedesmus pluvialis)			
	(Contd. on page 11)			

...page .



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

rade name: Ak	epox 2010 Component B			
		(Contd. of page 10)		
EC50	2,100 mg/l (BES) (OECD 209)	(comar or page 10)		
	79 mg/l (Scenedesmus quadricauda)			
EC10/16h	658 mg/l (pseudomonas putida)			
EC50/48h	230 mg/l (daphnia magna) (OECD 202)			
EC0	640 mg/l (Scenedesmus quadricauda)			
EC50/16h	658 mg/l (pseudomonas putida)			
EC50/30min	71.4 mg/l (Photobac. phosphoreum)			
	400 mg/l (pseudomonas putida)			
IC5/96h	640 mg/l (Scenedesmus quadricauda)			
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)			
NOEC/21d	51 mg/l (daphnia magna) (OECD211)			
EC50/72h	770 mg/l (green alge) (OECD 201)			
	770 mg/l (Pseudokirchneriella subcapitata)			
LC50/96h	645 mg/l (goo)			
	10 mg/l (lepomis macrochirus)			
	460 mg/l (Pimephales promelas)			
1477-55-0 m	-phenylenebis(methylamine)			
EC50/48h	15.2 mg/l (daphnia magna)			
EC50/72h	12 mg/l (Scenedesmus subspicatus)			
	20.3 mg/l (selenastrum capricornutum)			
LC50/96h >100 mg/l (Oncorhynchus mykiss)				
	87.6 mg/l (Oryzias latipes)			
	>100 mg/l (Zebrabärbling)			
84852-15-3	-nonylphenol, branched			
EC50/96h	0.41 mg/l (green alge)			
EC50/48h	0.14 mg/l (daphnia magna)			
NOEC/21d	0.024 mg/l (daphnia magna)			
EC50/72h	1.3 mg/l (Scenedesmus subspicatus)			
LC50/96h	0.135 mg/l (Pimephales promelas)			
108-95-2 ph	enol			
EC50/24h	21 mg/l (BO)			
EC50/96h	61.1 mg/l (green alge)			
EC50/48h	3.1 mg/l (daphnia magna)			
LC50/96h	8.9 mg/l (Oncorhynchus mykiss)			
· 12.2 Persist				
degradabilit				
• 12.3 Bioacci	umulative potential No further relevant information available. No further relevant information available.			
· Ecotoxical ef				
· Remark:	Harmful to fish			
- Additional ed	ological information:			

Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water · 12.5 Results of PBT and vPvB assessment

· General notes:

PBT: Not applicable.√PvB: Not applicable.

(Contd. on page 12)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

• 12.6 Other adverse effects No further relevant information available.

(Contd. of page 11)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

•	Euro	эρ	<u>ean</u>	wa	ste	ca	taı	og	ue	Э
			~ ~							

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:

• Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

acetone

SECTION 14: Transport information

· <u>14.1 UN-Number</u> · <u>ADR, IMDG, IATA</u>	UN2735
14.2 UN proper shipping name	
· <u>ADR</u>	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, m-phenylenebis(methylamine)), ENVIRONMENTALLY HAZARDOUS
· <u>IMDG</u>	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, m-phenylenebis(methylamine)), MARINE POLLUTANT
· <u>IATA</u>	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, m-phenylenebis(methylamine))

· 14.3 Transport hazard class(es)

· ADR





· <u>Class</u> 8 (C7) Corrosive substances.

· Label

· IMDG





· Class 8 Corrosive substances.

· Label

(Contd. on page 13)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

(Contd. of page 12)

IATA



· Class 8 Corrosive substances.

· Label

· 14.4 Packing group · ADR, IMDG, IATA

Ш

· 14.5 Environmental hazards:

· Marine pollutant: Nο

Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Corrosive substances.

· Danger code (Kemler): · EMS Number: F-A,S-B · Segregation groups Alkalis · Stowage Category

· Segregation Code SG35 Stow "separated from" acids.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category Ε · Tunnel restriction code

5L · Limited quantities (LQ)

 Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. · UN "Model Regulation": (ISOPHORONEDIAMINE,

PHENYLENEBIS(METHYLAMINE)), 8, III, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the

application of lower-tier

200 t requirements

(Contd. on page 14)



(Contd. of page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

Qualifying quantity (tonnes) for the

application of upper-tier

500 t

requirements

REGULATION (EC) No 1907/2006

Conditions of restriction: 3 ANNEX XVII

· Regulation (EU) No 649/2012

84852-15-3 4-nonylphenol, branched

Annex I Part 1 Annex I Part 2

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

84852-15-3 4-nonylphenol, branched

 VOC EU 177.6 g/l

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H301 Toxic if swallowed. Relevant phrases

> Harmful if swallowed. H302 H311 Toxic in contact with skin. H312 Harmful in contact with skin.

Causes severe skin burns and eye damage. H314

H317 May cause an allergic skin reaction. Causes serious eye damage. H318 Causes serious eye irritation. H319

Toxic if inhaled. H331 H332 Harmful if inhaled.

Suspected of causing genetic defects. H341

H361fd Suspected of damaging fertility. Suspected of damaging the unborn

May cause damage to organs through prolonged or repeated exposure. H373

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

· Recommended restriction of use

refer to Technical Data Sheet (TDS)

Department issuing SDS:

Laboratory Dieter Zimmermann

· Contact:

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 15)



according to 1907/2006/EC, Article 31

Printing date 12.07.2018 Version number 7 Revision: 12.07.2018

Trade name: Akepox 2010 Component B

(Contd. of page 14)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

 * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB