

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

COLOURING TINT LIQUID FOR AKEPOX

Article number:

11270, 11271, 11272, 11273, 11274, 11275, 11276, 11277, 11278, 11279, 11280, 11281, 11282, 11283, 11284, 11285, 11286, 11287, 11288, 11289, 11290, 11291, 11235, 11236, 11237, 11238, 11239, 11240, 11241, 11242, 11251, 11252, 11253, 11254, 11255, 11256, 11257

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Stainer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 NürnbergTel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

Signal word

Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 1)

- | | |
|--|---|
| <ul style="list-style-type: none"> · <u>Hazard statements</u> · <u>Precautionary statements</u> · <u>Additional information:</u> · <u>Labelling of packages where the contents do not exceed 125 ml</u> · <u>Hazard pictograms</u> · <u>Signal word</u> · <u>Hazard-determining components of labelling:</u> · <u>Hazard statements</u> · <u>Precautionary statements</u> · 2.3 Other hazards · <u>Results of PBT and vPvB assessment</u> · <u>PBT:</u> · <u>vPvB:</u> | <p>bisphenol F-(epichlorhydrin); epoxy resin
1.6-hexanediol diglycidyl ether
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)</p> <p>H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.</p> <p>P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p>Contains epoxy constituents. May produce an allergic reaction.</p> |
| |   <p>GHS07 GHS09</p> |
| | <p>bis[4-(2,3-epoxypropoxy)phenyl]propane
bisphenol F-(epichlorhydrin); epoxy resin
1.6-hexanediol diglycidyl ether
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)</p> <p>H317 May cause an allergic skin reaction.</p> <p>P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> |

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019







Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 2)

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

Description: Mixture: consisting of the following components.

Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	bis[4-(2,3-epoxypropoxy)phenyl]propane  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	bisphenol F-(epichlorhydrin); epoxy resin  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Skin Sens. 1, H317	12.5-25%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	1,6-hexanediol diglycidyl ether  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<12.5%
CAS: 123-26-2 EINECS: 204-613-6 Reg.nr.: 01-2120783565-42-xxxx	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)  Skin Sens. 1B, H317 Aquatic Chronic 3, H412	1-5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information:** Take affected persons out into the fresh air. Position and transport stably in side position.
- After inhalation:** Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:** If skin irritation continues, consult a doctor. Immediately wash with water and soap and rinse thoroughly.
- After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

- Information for doctor:** Allergic reactions
The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight ≤ 300 . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

- Hazards:** Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 3)

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from reducing agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Keep container tightly sealed.

· **7.3 Specific end use(s)**

No further relevant information available.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	DNEL (Kurzzeit-akut)	0.75 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	12.25 mg/m ³ Air (ARB)

9003-36-5 bisphenol F-(epichlorhydrin); epoxy resin

Oral	DNEL (Langzeit-wiederholt)	6.25 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.0083 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	104.15 mg/kg bw/day (ARB)
		62.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	29.39 mg/m ³ Air (ARB)
		8.7 mg/m ³ Air (BEV)

16096-31-4 1.6-hexanediol diglycidyl ether

Dermal	DNEL (Langzeit-wiederholt)	2.8 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	2.9 mg/m ³ Air (ARB)

· PNECs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC (wässrig)	10 mg/l (KA)
	0.0006 mg/l (MW)
	0.006 mg/l (SW)
	0.018 mg/l (WAS)
	0.196 mg/kg Trockengew (BO)
PNEC (fest)	0.0996 mg/kg Trockengew (MWS)
	0.996 mg/kg Trockengew (SWS)

9003-36-5 bisphenol F-(epichlorhydrin); epoxy resin

PNEC (wässrig)	10 mg/l (KA)
	0.0003 mg/l (MW)
	0.003 mg/l (SW)
	0.0254 mg/l (WAS)
	0.237 mg/kg Trockengew (BO)
PNEC (fest)	0.0294 mg/kg Trockengew (MWS)
	0.294 mg/kg Trockengew (SWS)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 5)

16096-31-4 1.6-hexanediol diglycidyl ether

PNEC (wässrig)	0.00115 mg/l (MW)
	0.0115 mg/l (SW)

- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended. After use of gloves apply skin-cleaning agents and skin cosmetics. Skin protection agent recommendation for preventive skin shelter without use of protective gloves:
 ARRETIL (<http://www.stoko.com>)
 Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
 STOKO EMULSION (<http://www.stoko.com>)
 Skin protection recommendation for skin cleaning after product handling:
 Kresto Classic (<http://debstoko.com>)
 Skin protection agent recommendation for skin aftercare:
 STOKO VITAN (<http://www.stoko.com>)
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times´ data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019


Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 6)

- Penetration time of glove material Value for the permeation: Level ≤ 2 , 30 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
 - Fluorocarbon rubber (Viton)
 - Vitoject (KCL, Art_No. 890)
 - Butoject (KCL, Art_No. 897, 898)
 - Nitrile rubber, NBR
 - Camatril (KCL, Art_No. 730, 731, 732, 733)
 - Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable:
 - Butoject (KCL, Art_No. 897, 898)
 - Nitrile rubber, NBR
 - Camatril (KCL, 730, 731, 732, 733)
 - Butoject (KCL, Art_No. 897, 898)
 - Butyl rubber, BR
- Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong material gloves
 - Nitrile rubber, NBR
- Eye protection:


Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties**· General Information· Appearance:

Form: Fluid
 Colour: According to product specification

· Odour: Specific type· Odour threshold: Not determined.· pH-value: Not applicable· Change in condition

Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: > 200 °C

· Flash point: Not applicable.· Flammability (solid, gas): Not applicable.· Decomposition temperature: Not determined.· Auto-ignition temperature: Product is not selfigniting.· Explosive properties: Product does not present an explosion hazard.· Explosion limits:

Lower: Not determined.
 Upper: Not determined.

· Vapour pressure at 20 °C: 2 hPa· Density at 20 °C: 1.55 g/cm³ ([1.30 - 1.73 g/cm³])· Relative density Not determined.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 7)

· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	10,000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
· 10.3 Possibility of hazardous reactions	Reacts with reducing agents. Reacts with strong acids. Reacts with strong alkali. Violent reactions with -NHx, -OH and -SH- groups.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	Carbon monoxide and carbon dioxide Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects	
· Acute toxicity	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	13,740 mg/kg
------	------	--------------

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	LD50	15,000 mg/kg (rat)
Dermal	LD50	23,000 mg/kg (rabbit)

9003-36-5 bisphenol F-(epichlorhydrin); epoxy resin

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
		>2,000 mg/kg (rat)

16096-31-4 1.6-hexanediol diglycidyl ether

Oral	LD50	1,400 mg/kg (mouse)
		8,500 mg/kg (rat)
Dermal	LD50	>4,900 mg/kg (rabbit)
	LD50	>4,900 mg/kg (rat)
Inhalative	LC50/4 h	>100 mg/l (mouse)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 8)

LC50/48h	23.1 mg/l (green alge)
----------	------------------------

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

- Aquatic toxicity:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	2.7 mg/l (daphnia magna)
NOEC/21d	0.3 mg/l (daphnia magna)
EC50/72h	9.4 mg/l (selenastrum capricornutum)
LC50/96h	1.5 mg/l (Oncorhynchus mykiss)

9003-36-5 bisphenol F-(epichlorhydrin); epoxy resin

IC50	>100 mg/l (BES)
	>100 mg/l (bacteria)
EC50/48h	2.55 mg/l (daphnia magna) (OECD 202: Part I)
NOEC	0.3 mg/kg (daphnia magna) (OECD 211)
EC50/72h	1.8 mg/l (green alge) (OECD 201)
	1.8 mg/l (Selenastrum capricornutum)
LC50/96h	0.55 mg/l (piscis) (OECD 203)
	2.54 mg/l (Leuciscus idus)
	0.55 mg/l (Oncorhynchus mykiss)

16096-31-4 1.6-hexanediol diglycidyl ether

EC50/48h	67 mg/l (daphnia magna)
EC50/48h	67 mg/l (daphnia magna)
LC50/96h	1.1 mg/l (goo)
	30 mg/l (Oncorhynchus mykiss)
LC50/72h	30 mg/l (Oncorhynchus mykiss)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:Remark:

Toxic for fish

Additional ecological information:General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 9)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Alcohol

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN3082

- **14.2 UN proper shipping name**
- **ADR** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, bisphenol F-(epichlorhydrin); epoxy resin)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, bisphenol F-(epichlorhydrin); epoxy resin), MARINE POLLUTANT
- **IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, bisphenol F-(epichlorhydrin); epoxy resin)

· **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 9 (M6) Miscellaneous dangerous substances and articles.
- **Label** 9

- **IMDG, IATA**



- **Class** 9 Miscellaneous dangerous substances and articles.
- **Label** 9

· **14.4 Packing group**

- **ADR, IMDG, IATA** III

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 10)

<ul style="list-style-type: none"> · 14.5 Environmental hazards: · <u>Marine pollutant:</u> · <u>Special marking (ADR):</u> · <u>Special marking (IATA):</u> 	Product contains environmentally hazardous substances: Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · <u>Danger code (Kemler):</u> · <u>EMS Number:</u> · <u>Stowage Category</u> 	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · <u>Transport/Additional information:</u> · <u>ADR</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u> · <u>Transport category</u> · <u>Tunnel restriction code</u> 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 -
<ul style="list-style-type: none"> · <u>IMDG</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u> 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · <u>UN "Model Regulation":</u> 	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 0.0 g/l

(Contd. on page 12)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.08.2019

Version number 9

Revision: 07.08.2019

Trade name: COLOURING TINT LIQUID FOR AKEPOX

(Contd. of page 11)

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use

refer to Technical Data Sheet (TDS)

· Department issuing SDS:

Laboratory

· Contact:

Dieter Zimmermann
 Elke Hake
 Fon ++49 (0)911 64296-59
 @mail E.Hake@akemi.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organisation
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 REACH directive 1907/2006/EC

· Sources

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC